Automatic Strapping Machine
Stand Model WG-22XN



FEATURES:

1.Rapid speed: 2.0sec/per cycle, 30cycles/per min.

2.Easy Maintenance: No Greasing, Mechanism is stable and durable, Easy operation.

3.Tension Adjustment: Can be adjustable at well,Max. tension is over 90kgs.

4.Precision Structure: Main machinei¯s component is made of aluminum alloy. Control System is compatible.

5.Add on a safety device, built for 24 hrs continuous operation.

6.Easy loading or unloading: To load or unload the strapping roll is convenient due to the dispenser is placed outside.

7.Extensive applications: can be independent operation or combine with other machines for unmanned

8.Electric appliance adopted: i±LGi± PLC control, French i±TEi± and photoelectric switch control(WG-22XA)

9.Optional: any arch size

Model	WG-22XN
Strapping tension	40-700Nadjustable
Strapping speed	2.0Sec./Strap
Strap width	8-19mm
Arch size	800x600mm
Power supply	380V/50-60Hz, 220V
Power consumption	0.85KVA
Machine size	1410X600X1540mm
Machine weight	250kg

Automatic Strapping Machine
Vertical Model DBA-130A



Model	DBA-130A
Strapping tension	100-700Nadjustable
Strapping speed	2.0Sec./Strap
Strap width	9-15mm
Chute size	L 1000mm
Power supply	110,220V/50-60Hz
Power consumption	0.5KVA
Machine size	1860X560X1500mm
Machine weight	140kg

Semi-Automatic Strapping Machine
KZBI



Detailed Product Description

Features:
1) Strapping tension: 5 - 60kg
2) Strapping speed: 2.0sec./strap
3) Strap width: 6 - 15mm
4) Controlled PP strap cooling time, which can make PP strap to fasten well in any time
5) Electricity saving device, the motor automatically stops running after 35 sec. and pauses to reduce normal wearing and to prolong the m/c life
6) With non-fast heater plate, it will increase the work efficiency
7) Advanced P.C.B microchip circuit board control system
8) Less malfunction and easy maintenance
9) Standard accessories, stable quality and durable material

Outer packing:
Carton dimensions: 920 x 600 x 860mm
N.W.: 90kg
G.W.: 105kg

Model	KZB-I
Strapping tension	40-480Nadjustable
Strapping speed	2.2Sec./Strap
Strap width	6-15mm
Power supply	110V, 220-240V/50-60Hz
Power consumption	0.4KVA
Machine size	835X560X725mm
Machine weight	90kg